# Safety Data Sheet

BOSS" 139 Fire Mortar

#### Section 1. Identification

Product Identifier

BOSS" 139 Fire Mortar

Synonyms

03422BK10

Manufacture Stock

03422BK10; C39040BK

Numbers

Recommended use Uses advised against

Refer to Technical Data Refer to Technical Data

Manufacturer Contact

Address

SOUDAL Accumetric

350 Ring Road

Elizabethtown, KY, 42701

**USA** 

Phone

Emergency

Fax

N/A

Phone

(270) 769-3385

(800) 424-

9300 Chemtrec

## Section 2. Hazards I dentification

SKIN CORROSION/IRRITATION - Category 2

Signal Word Pictogram Danger



Hazard Statements Causes serious eye damage

Causes skin irritation

Precautionary Statements

Response If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsing.

If on skin: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

Read label before use.

Take off contaminated clothing and wash it before reuse.

Prevention Wash hands thoroughly after handling.

Wear eye protection/face protection.

Wear protective gloves.

Storage N/A
Disposal N/A

Ingredients of unknown 0%

toxicity

Hazards not Otherwise None known

Classified

# Section 3. Ingredients

CAS	Ingredient Name	Weight %
1344-09-8	Sodium silicate	15% - 35%
7732-18-5	Water	20% - 40%

Occupational exposure limits, if available, are listed in Section 8.

#### Section 4. First-aid Measures

Ingestion Do not induce vomiting. Immediately drink two glasses of water.

Never give anything to an unconscious person. Get medical

attention.

Inhalation Remove to fresh air. If symptoms persist, obtain appropriate

medical attention.

Skin Contact Thoroughly wash exposed skin with soap and water.

Eye Contact Flush eyes gently with water for at least 15 minutes, lifting

eyelids occasionally; get prompt medical attention.

Comments Treat according to person's condition and specifics of exposure.

# Section 5. Fire Fighting Measures

Suitable Extinguishing

Media

Unsuitable

Extinguishing Media

Unusual Fire or Explosion Hazards

Special Fire Fighting

Procedures

Extinguishing Media

Flammability Limits in

Air

Hazardous

**Decomposition Products** 

N/A

N/A

None known

Breathing apparatus required when fighting fires in enclosed spaces.

Carbon Dioxide, Dry

Chemical, Foam Use water fog to cool material

in vicinity of fire. Not applicable

Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition

products: None known

#### Section 6. Accidental Release Measures

Steps to be taken in case of spill or release

Observe all personal protection equipment recommendations. Soak up with inert absorbent. Store in a partly filled, closed container until disposal. Prevent product from entering drains. Local, state and federal regulations may apply to releases and disposal of this material, as well as those materials and items employed in cleanup of releases.

# Section 7. Handling and Storage

Handling Avoid eye contact and repeated prolonged contact with the skin.

Keep out of reach from children.

Storage Store in a cool dry place. Protect from freezing and excessive

heat. Store away from caustics and oxidizers.

# Section 8. Exposure Controls/Personal Protecction

Occupational Exposure

Limits

Ingredient Name	ACGIH TLV	OSHA PEL	STEL
Sodium silicate	N/A	N/A	N/A
Water	0	N/A	N/A

Personal Protective

Equipment

Respiratory Protection

If engineering controls do not maintain airborne concentrations of

hazardous ingredients below TLV, then a NIOSH/MSHA approved organic vapor respirator should be used. Not required under

normal usage and adequate ventilation.

Ventilation Good general ventilation should be sufficient.

**Skin Protection** Impervious gloves are suggested.

N/A

**Eye Protection** Safety goggles or glasses with side shields are recommended.

Ingestion Do not eat, drink or smoke during work.

# Section 9. Physical and Chemical Properties

Physical State	Paste
Color	Black
Odor	Slight
Odor Threshold	N/A
Solubility	Dilutable in
	wet stage
Partition coefficient Water/n-	N/A
octanol	
Viscosity	750,000 cPs
Specific Gravity	1.85
Density Ibs/Gal	15.439
Pounds per Cubic Foot	115.49173
Flash Point	Not
	determined
FP Method	N/A
Ph	12
Melting Point	OC
Boiling Point	100C
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	Slower than
	n-Butyl
	acetate
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A
Vapor Pressure	Not
	determined
Vapor Density	Lighter than
	air

NoteThe above information is not intended for use in preparing product specifications. Contact SOUDAL Accumentric before writing specifications.

### Section 10. Stability and Reactivity

Conditions to Avoid

Excessive heat and freezing.

Hazardous

Will not occur

Polymerization

Chemical Stability

Stable

Materials to Avoid / Incompatibility

Reacts with acids, ammonium salts, reactive metals, and some

organics.

# Section 11. Toxicological Information

Special Hazard Information on Components

No known applicable information.

Component Toxicology

No known applicable information.

Information

### Section 12. Ecological Information

High pH is harmful to aquatic life. **Environmental Effects** 

Environmental Fate and Complete information is not yet available.

Distribution

Fate and Effects in

Complete information is not yet available.

Waste Water Treatment

**Plants** 

### Section 13. Disposal

Waste Disposal Method We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes. This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

# Section 14. Transport Information

UN Number	N/A
UN Proper Shipping Name	N/A
DOT Classification	N/A
Packing Group	N/A

Air Shipment (IATA) ICAO/IATA Class: 2.1

UN/ID Number: 1950 Label: 2.1 Packaging Group: - Proper Shipping Name: AEROSOLS, flammable, n.o.s.

Ocean Shipment (IMDG)

Not subject to IMDG

code.

Road Shipment Not subject to DOT Information (DOT) regulations.

### Section 15. Regulatory Information

None

The contents of this MSDS comply with the OSHA Hazard

Communication Standard 29 CFR 1910.1200.

TSCA Status All chemical substances found in this product comply with the

Toxic Substances Control Act inventory reporting requirements.

California Proposition This product contains the following chemical(s) listed by the State

of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth

defects or other reproductive harm: Carbon black (1333-86-4)

SARA Title III Section

302 Extremely

Hazardous Substances

SARA Titre III Section None

304 CERCLA Substances

dangereuses

Disclaimer

SARA Title III Section None present or none present in regulated quantities.

313 Toxic Chemicals

Massachusetts Carbon black (1333-86-4)
New Jersey Carbon black (1333-86-4)
Pennsylvania Carbon black (1333-86-4)

#### Section 16. Other Information

Revision Date 5/26/2015

The data contained herein is based upon information that SOUDAL Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.