

# MSDS Document

## Product BOSS® 315 RTV Silicone Sealant

### 1. Chemical Product and Company Identification

**Trade Name of this Product** BOSS® 315 RTV Silicone Sealant

**Synonyms:** 03207BL01, 03207CL01, 03207WH01

**MSDS ID** BOSS315

**Manufacturer**

Accumetric, LLC  
350 Ring Road  
Elizabethtown, KY 42701


**Phone Number**

(270) 769-3385

**Emergency Phone**

CHEMTREC (800) 424-9300

**Revision Date** 12/3/2012



### 2. Composition and Information on Ingredients

Ingredient	CAS Number	Weight %	ACGIH TLV	PEL	STEL
Methyltriacetoxysilane	4253-34-3	1% - 5%	TWA 10ppm	TWA 10ppm	15ppm
Ethyltriacetoxysilane	17689-77-9	1% - 5%	TWA 10ppm	TWA 10ppm	15ppm
Distillates (petroleum), hydrotreated middle	64742-46-7	<= 7.0 %	5 mg/m3	5 mg/m3	10 mg/m3

### 3. Hazard Identification

**Eye Contact**

Direct contact may cause mild irritation.

**Skin contact**

May cause mild irritation

**Inhalation**

Material is not likely to present an inhalation hazard at ambient conditions. However, if

material is heated or high vapor/aerosol concentrations are attained, central nervous system depression may occur, which is characterized by drowsiness, dizziness, confusion or loss of coordination.

**Ingestion**

Low ingestion hazard in normal use.

**Symptoms of Overexposure**

No known applicable information.

**Existing Conditions Aggravated by Exposure**

No known applicable information.

**Note**

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

**4. First Aid Information**

**Eye Contact**

Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes while holding the eyelids open. Obtain medical attention.

**Skin Contact**

No health effects expected. If irritation does occur, flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical advice.

**Inhalation**

Material is not likely to present an inhalation hazard at ambient conditions. If material is heated or vapor are generated, care should be taken to prevent inhalation. In case of exposure to vapor, move to fresh air.

**Ingestion**

If irritation or discomfort occur, obtain medical advice.

**Comments**

Treat according to person's condition and specifics of exposure.

**5. Fire Fighting Measures**

**Flash Point** >212F >100C

**Auto-ignition Temperature**

Not determined

**Extinguishing Media**

On large fires use dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical or water spray. Water can be used to cool fire exposed containers.

**Flammability Limits in Air**

Not determined

**Special Fire Fighting Procedures**

Self-contained breathing apparatus and protective clothing should be worn when fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

**Unusual Fire or Explosion Hazards**

None known

**6. Accidental Release Measures****Steps to be taken in case of spill or release**

Observe all personal protection equipment recommendations in Sections 5 and 8. Wipe or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

**Note**

See Section 8 for information about personal protective equipment for spills. Contact Accumetric, LLC if additional information is required.

**7. Handling and Storage****Handling**

Use adequate ventilation. Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid within exposure guidelines or use respiratory protection. Avoid eye contact.

**Storage**

Use reasonable care and store away from oxidizing materials. Keep container closed and store away from water or moisture. This material in its finely divided form presents an explosion hazard. Follow NFPA 654 (for chemical dusts) or 484 (for metal dusts) as appropriate for managing dust hazards to minimize secondary explosion potential.

**8. Exposure Controls and Personal Protection****Component Exposure Limits**

Component Name: Hydrotreated middle petroleum distillates

CAS Number: 64742-46-7

Exposure Limits: OSHA PEL (final rule) and ACGIH TLV for oil mists: TWA 5 mg/m<sup>3</sup>

Component Name: Ethyltriacetoxysilane  
CAS Number: 17689-77-9  
Exposure Limits: See acetic acid comments

Component Name: Methyltriacetoxysilane  
CAS Number: 4253-34-3  
Exposure Limits: See acetic acid comments

Acetic acid is formed upon contact with water or humid air.

### **Engineering Controls**

Local Ventilation: Recommended  
General Ventilation: Recommended

### **Eye Protection**

Use proper protection - safety glasses as a minimum.

### **Skin Protection**

Wash at mealtimes and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Suitable Gloves:

Handle in accordance with good industrial hygiene and safety practices.

### **Inhalation**

Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. IH personnel can assist in judging the adequacy of existing engineering controls.

### **Suitable Respirator**

Respiratory protection is not needed under ambient conditions. If vapor is generated when material is heated or handled, the following is advised. General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.

### **Personal Protective Equipment for Spills**

Eyes: Use full face respirator.

Skin: Wash at mealtimes and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Inhalation/Suitable Respirator: Respiratory protection recommended. Follow OSHA Respirator Regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

### Precautionary Measures

Avoid eye contact. Use reasonable care.

### Comment

Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid within exposure guidelines or use respiratory protection.

When heated to temperatures above 150C (300F) in the presence of air, product can form formaldehyde vapors. Physical and health hazard information is readily available on the Material Safety Data Sheet. When heated to temperatures above 150C in the presence of air, product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard, a known skin and respiratory sensitizer, and an irritant to the eyes, nose throat, skin and digestive system. Safe handling conditions may be maintained by keeping vapor concentrations within the OSHA Permissible Exposure Limit for formaldehyde.

### Note

These precautions are for room temperature handling. Use at elevated temperatures or aerosol/spray applications may require added precautions.

## 9. Physical and Chemical Properties

<b>Physical State</b>	Paste
<b>Specific Gravity</b>	1.007
<b>Color/Appearance</b>	Clear
<b>Odor</b>	Acetic Acid Odor
<b>pH</b>	Not Determined
<b>Boiling/Cond. Point</b>	Not Determined
<b>Melting/Freezing Point</b>	Not Determined
<b>Solubility</b>	Not Determined
<b>Evaporation Rate</b>	Not Determined
<b>VOC %</b>	29g/L (<3.0% wt)
<b>Viscosity</b>	Not Determined
<b>Vapor Density</b>	Not Determined
<b>Vapor Pressure</b>	Not Determined

### Note

The above information is not intended for use in preparing product specifications. Contact Accumetric LLC before writing specifications.

## 10. Stability and Reactivity

### Chemical Stability

Stable

### Hazardous Polymerization

Will not occur

### Conditions to Avoid

None known

### Materials to Avoid / Incompatibility

Oxidizing material can cause a reaction. Water, moisture or humid air can cause hazardous

vapors to form as described in Section 8.

#### **Hazardous Decomposition Products**

Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products:

Carbon oxides and traces of incompletely burned carbon compounds

Formaldehyde

Silicon dioxide

## **11. Toxicological Information**

#### **Special Hazard Information on Components**

No known applicable information.

## **12. Ecological Information**

#### **Environmental Fate and Distribution**

Complete information is not yet available.

#### **Environmental Effects**

Complete information is not yet available.

#### **Fate and Effects in Waste Water Treatment Plants**

Complete information is not yet available.

## **13. Disposal Considerations**

#### **RCRA Hazard Class (40 CFR 261)**

When a decision is made to discard this material, as received, is it classified as a hazardous waste? NO

State or local laws may impose additional regulatory requirements regarding disposal.

#### **Waste Disposal Method**

We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

## **14. Transportation Information**

#### **Voie terrestre DOT**

Pas assujetti au DOT

**Ocean Shipment (IMDG)**

Not subject to IMDG code.

**Air Shipment (IATA)**

Not subject to IATA regulations.

## 15. Regulatory Information

The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

**TSCA Status**

All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

**SARA Title III Section 302 Extremely Hazardous Substances**

None

**SARA Titre III Section 304 CERCLA Substances dangereuses**

None

**SARA Title III Section 311/312 Hazard Class**

Acute: No

Chronic: No

Fire: No

Pressure: No

Reactive: No

**SARA Title III Section 313 Toxic Chemicals**

None present or none present in regulated quantities.

**Note**

Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.

**California Proposition 65**

This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm:

None known

**Massachusetts**

Silica, amorphous (7631-86-9)

**New Jersey**

Dimethyl siloxane, hydroxy-terminated (70131-67-8)

Ethyltriacetoxysilane (17689-77-9)

Methyltriacetoxysilane (4253-34-3)

Silica, amorphous (7631-86-9)

Hydrotreated middle petroleum distillates (64742-46-7)

**Pennsylvania**

Dimethyl siloxane, hydroxy-terminated (70131-67-8)

Silica, amorphous (7631-86-9)

Hydrotreated middle petroleum distillates (64742-46-7)

**16. Other Information**

**Disclaimer**

The data contained herein is based upon information that Accumetric LLC believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.