

Christy's™

— PRODUCT INFORMATION & SPECIFICATIONS —



PRO-LUBE™

DESCRIPTION

Pro-Lube is a water dispersible, high performance pipe joint lubricant that has been certified by NSF for use in potable water supply systems. The creamy consistency allows the installer to apply a smooth, consistent coating to both gasket and pipe.

- Mixed fatty acid soap dispersed in glycols and water solvents with a clay pigment filler
- Does not dry out when gaskets are stored in sealed plastic bags or container
- Maintains soft paste consistency and color
- Ideal for all types of pipe (asbestos cement, cast iron, concrete, plastic and clay)
- Does not deteriorate natural or synthetic rubber or plastic gaskets
- Available in quart, gallon and 5 gallon

PRODUCT SPECIFICATIONS

NSF code 61 listed for use on potable water systems

Manufactured from environmentally friendly raw materials

Will not irritate the hands and is not toxic

| | |
|-------------------|---|
| Appearance (neat) | Soft amber paste |
| pH (1%) | 9.5 |
| Bulk Density | 9.3 lb / gal |
| Free Fatty Acid | 1-3% |
| Total Alkalinity | 100 mg KOH / g equivalent |
| Penetration | 300 - 350 1 / 10mm@77°F 200 - 250 1 / 10mm@0°F |

ESTIMATED USAGE CHART

| PIPE SIZE | LBS. PER 100 JOINTS | PIPE SIZE | LBS. PER 100 JOINTS |
|-----------|---------------------|-----------|---------------------|
| 4" | 3 | 30" | 22 |
| 6" | 4 | 36" | 28 |
| 8" | 5 | 42" | 32 |
| 10" | 6 | 48" | 40 |
| 12" | 9 | 54" | 45 |
| 15" | 11 | 60" | 54 |
| 18" | 13 | 66" | 60 |
| 21" | 16 | 72" | 67 |
| 24" | 17 | 78" | 70 |
| 27" | 19 | 84" | 77 |

T. Christy Enterprises, Inc.
655 E Ball Rd • Anaheim, CA 92805
Tel: (714) 507-3300 • Fax: (714) 507-3310
www.tchristy.com • 800-BLU-GLUE