



The 3M™ Direct Bury Splice Kit DBR/Y-6 is used to electrically connect two or more pre-stripped copper wires and moisture seal the connection for direct burial.

3M™ Direct Bury Splice Kit DBR/Y-6

3M™ Direct Bury Splice Bulk DBR/Y-6 is a premium moisture-resistant connector that is used to electrically connect and moisture seal thicker insulation wire. Consists of a 3M™ Spring Connecto R/Y and a high impact, UV-resistant tube prefilled with moisture-resistant grease. UL-listed for direct bury and rated for 600V.

Agency Approvals	UL
Conductor Sizes	10 AWG, 18 - 10 AWG, 18 AWG
Connection Type	Wire
Connector Style	Direct Bury
ETIM Class 5.0	EC000306
Family	Direct Bury
Flame Retardant	UL-94 V-2
Maximum Wire Gauge	10 AWG
Minimum Wire Gauge	18 AWG
Operating Temperature (Celsius)	-40 to 105 Degree Celsius
Operating Temperature (Fahrenheit)	-40 to 221 Degree Fahrenheit
RoHS 2011/65/EU Compliant	Yes
RoHS EU Comments	RoHS 2011/65/EU compliant without exemption *Important RoHS information
Trademark	Scotchlok

DISTRIBUTED BY:

T. Christy Enterprises, Inc.

655 E. Ball Rd. • Anaheim, CA 92805

Tel: (714) 507-3300 • Fax: (714) 507-3310

www.TChristy.com • 800-BLU-GLUE