



TECHNICAL SPECIFICATIONS

- Flex Pro PVC Solvent Cement can be used for pressure and non-pressure pool, spa, bath, irrigation, potable water, DWV, sewer, drain, gas duct and conduit applications. This product is not for use with compressed air or gases.
- Meets ASTM D-2564.
- Low VOC formulation meets the requirements of California South Coast Air Quality Management District. For US Green Building Council LEED projects, low VOC solvent cements can earn credits toward green building certification.
- Appropriate Christy's clear or purple primer should be used where required by local code or to meet UPC code.
- Package sizes: 1/4 pint, 1/2 pint, Pint, Quart, Gallon.
- NSF and U.P. Code.



How-to Video



T. Christy Enterprises, Inc.

655 E. Ball Rd. • Anaheim, CA 92805

Tel: (714) 507-3300 • Fax: (714) 507-3310

www.TChristy.com • 800-BLU-GLUE

Flex Pro PVC Pipe Cement

Preferred for use with flexible PVC piping

Working with flexible PVC pipe? Reach for a solvent cement that's specially formulated for the unique challenges of flexible joints, Christy's Flex Pro. Flex Pro is used for pool, spa, water gardening, irrigation and other applications. It forms flexible, high-strength water resistant joints in both flex-to-flex and flex-to-fitting applications.

- **Uniquely resilient to vibrations** common with spa and swimming pool installations.
- **In irrigation**, use with flexible risers and drop lines.
- **Clear, medium bodied**, fast setting.
- **Recommended for all flexible or rigid PVC** through 6" diameter, Schedule 80 through 4" diameter.

Can Size	Part Number	Units per Case
1/4 Pint	RH.FLEX.QP	24
1/2 Pint	RH.FLEXL.HP	24
Pint	RH.FLEX.PT	12
Quart	RH.FLEX.QT	12
Gallon	RH.FLEX.1	6