

Q: What is the difference between PVC solvent cement and PVC glue?

A: Solvent welding is a chemical process that uses a primer, or the cement itself, to soften the surface of plastic pipe and fittings in order to weld, or fuse them together. This requires a tight, or interference fit. The solids contained in the solvent cement will then fill the gap between the pipe and fitting. Glue such as PVC glue, on the other hand, is only a bonding cement and will not work with an interference fit.

Q: What is the purpose of a cleaner?

A: Primers pre-soften the surface of the pipe and fitting before the solvent cement is applied so that maximum fusion can take place. They also remove grease, dirt, and foreign matter from the surface of the pipe and fitting prior to application of the primer and cement.

Q: What is Set Time vs Cure Time?

A: The Set Time is the amount of time the joint is to be left undisturbed before handling. The Cure Time is the amount of time it takes the joint to be completely set and ready for pressure to be applied.

Q: What does Low VOC mean?

A: VOC stands for Volatile Organic Compounds which are emissions from materials. Low VOC products contribute to cleaner air. The South Coast Air Quality Management District (“SCAQMD”), an air pollution control agency for southern California, sets strict emissions control requirements (Rule 1168/316A) which Christy’s meets with its Low VOC products. Many other states have adopted, or are in process of adopting, SCAQMD Rule 1168/316A emission limits and/or similar limits for solvent cements and primers.

Q: Am I required to use Low VOC solvent cements and Primers? Which states require the use of Low VOC solvent cements and primers?

A: Low VOC solvent cements and primers are currently required in California, Maryland, New Jersey and Connecticut. Requirements are also under consideration in several other states, including New York, Rhode Island, and Maine. Even where not required, Low VOC products are a good idea because they contribute to cleaner air and a healthier environment.

Q: How are the Low VOC solvent cements and primers different than non-Low VOC solvent cements and primers?

A: Christy's Low VOC solvent cements and primers provide the same performance, have the same installation properties, but are better for the environment and more user-friendly than non-Low VOC products.

Q: Should the primer dry before the solvent cement is applied?

A: No. The primer must be wet and fluid. The purpose of the primer is to soften the joining surfaces of the pipe and fitting allowing proper penetration and dissolution of joining surfaces prior to solvent cement application. This step is specifically recommended for large diameters, PVC Schedule 80, CPVC piping and cold weather installations.

Q: Will the dauber inside a quart can work on an 8-inch diameter pipe and fitting?

A: No. For 4-inch and larger diameter piping, we recommend the use of 4-inch swab to apply our primers and solvent cements. A can dauber is appropriate for use on pipe diameters that are approximately twice the size of the dauber diameter.

Q: Since there are so many primers and solvent cements available, how should I select the correct products for my job?

A: Identify the parameters of the particular application:

- Pipe material - PVC, CPVC, ABS
- Schedule or SDR of piping - Sch.40, Sch.80, SDR21, etc.
- Pipe diameter
- Working pressure of piping system
- Ambient temperature at the time of installation
- Temperature of media conveyance within the piping system
- Type of media being conveyed within the piping system - water, specific chemicals, etc.
- Other variables which may affect application and/or piping system

Q: What is the shelf life of primers and solvent cements?

A: Christy's primers, PVC, CPVC and ABS solvent cements: 3 years shelf life
Christy's primers and solvent cements have expiration dates imprinted on the outside of the case boxes and the manufactured date imprinted on the bottom of each can.

Q: Where can I obtain information about Christy's products?

A: www.TChristy.com

Consult the Christy's Product Guides for more information or contact your local Christy's sales representatives for recommendation. If further technical assistance is required, contact us at 1-800-BLU-GLUE to speak to Customer Service.

Q: Will CPVC solvent cement work on a PVC piping installation?

A: Yes. CPVC solvent cement technically will work on PVC piping. However, we recommend that the correct Weld-On primer and PVC solvent cement for the particular application should be used. Please note that PVC solvent cement, because of temperature limitations, is not recommended for CPVC piping

Q: Why can gray CPVC solvent cement NOT be used on riser piping for a hot and cold potable water application?

A: According to International and Uniform Plumbing Codes (IPC and UPC), a purple primer and orange CPVC solvent cement must be used on all CPVC potable water applications using gray CPVC IPS (Iron Pipe Size) riser piping.

Q: How much time should be allowed before a 6-inch diameter CPVC piping system installed at 85°F (29°C) be hydrostatically pressure tested??

A: The appropriate cure time for the stated application is a minimum of 24 hours after the last joint of the pipe system is installed. Then the system can be hydrostatically pressure tested. Set time is time required before a joint can be carefully handled. Cure time is the time required before the piping system can be hydrostatically tested at a maximum of 150% of the systems design pressure.



FREQUENTLY ASKED QUESTIONS

Q: How much time should be allowed before a 6-inch diameter CPVC piping system installed at 85°F (29°C) be hydrostatically pressure tested??

A: The appropriate cure time for the stated application is a minimum of 24 hours after the last joint of the pipe system is installed. Then the system can be hydrostatically pressure tested. Set time is time required before a joint can be carefully handled. Cure time is the time required before the piping system can be hydrostatically tested at a maximum of 150% of the systems design pressure.

Please refer to the typical initial set and cure time chart for all Christy's products. Ask your Christy's Rep, or visit www.tchristy.com