

**Safety Data Sheet  
acc. to OSHA HCS**

Printing date 05/19/2015

Version 4

Reviewed on 05/19/2015

**1 Identification of the substance/mixture and of the company/undertaking**

· **Product identifier** Polyken 1027 Liquid Adhesive

· **Trade name:** Polyken 1027 Liquid Adhesive

· **Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use**

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Product category** PC1 Adhesives, sealants

· **Process category**

PROC10 Roller application or brushing

PROC11 Non industrial spraying

· **Environmental release category**

ERC8d Wide dispersive outdoor use of processing aids in open systems

ERC10b Wide dispersive outdoor use of long-life articles and materials with high or intended release (including abrasive processing)

· **Article category** AC30 Other articles with intended release of substances

· **Application of the substance / the mixture** Coating adhesive

· **Uses advised against** -

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:** Seal For Life Industries - Polyken™

· **Contact details**

Seal For Life Industries LLC  
25 Forge Parkway, Franklin MA, 02038 USA  
Tel. (+1) 800-343-7875, Fax. (+1) 800-328-4822, Email: franklin@sealforlife.com

Seal For Life Industries LLC  
2320 Bowling Green Road, Franklin KY, 42134 USA  
Tel. (+1) 800-343-7875, Fax. (+1) 800-328-4822, Email: franklin@sealforlife.com

Seal For Life Industries BVBA  
Nijverheidsstraat 13, B-2260 Westerlo, Belgium  
Tel. +32 14 72 25 00, Fax. +32 14 72 25 70, Email: belgium@sealforlife.com

Seal For Life Industries - Stopaq B.V.  
Gasselterstraat 20, 9503JB Stadskanaal, the Netherlands  
Tel +31 599 696 170, Fax +31 599 696 177, Email: info@sealforlife.com

Seal For Life Industries Mexico S de R.L. de C.V.  
Calle 11 Norte 11002, Cd Ind Nueva Tijuana, Tijuana Baja California, Mexico, CP 22500  
Tel USA: +1 858 633 9797, Tel Mx: +52 664 647 4397, Fax USA: +1 858 633 9740, Fax Mx: +52 664 607 9105  
Email: mexico@sealforlife.com

Seal For Life India Private Ltd.  
Plot17, GIDC Savli, Vadodara, Gujarat, Baroda, India - 391775  
Tel: +91 266 726 4721, Fax: +91 266 726 4724, Email: india@sealforlife.com

· **Information department:** Occupational product safety department of Seal For Life Industries

· **Emergency telephone number:**

For worldwide emergency assistance call CHEMTREC (24 hours):

Within USA/Canada 1-800-424-9300; Outside USA/Canada +1 703-527-3887 (collect calls accepted)

(Contd. on page 2)

**Safety Data Sheet  
 acc. to OSHA HCS**

Printing date 05/19/2015

Version 4

Reviewed on 05/19/2015

**Trade name: Polyken 1027 Liquid Adhesive**

(Contd. of page 1)

**2 Hazard(s) identification**

· **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.  
 STOT RE 2 H373 May cause damage to the central nervous system through prolonged or repeated exposure.  
 Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS09 Environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.  
 STOT SE 3 H336 May cause drowsiness or dizziness.

· **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02



GHS07



GHS08



GHS09

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Distillates (petroleum), light distillate hydrotreating process, low-boiling (note P)  
 toluene  
 methanol

· **Hazard statements**

H225 Highly flammable liquid and vapor.  
 H315 Causes skin irritation.  
 H361 Suspected of damaging fertility or the unborn child.  
 H336 May cause drowsiness or dizziness.  
 H373 May cause damage to the central nervous system through prolonged or repeated exposure.  
 H304 May be fatal if swallowed and enters airways.  
 H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 P241 Use explosion-proof electrical/ventilating/lighting/equipment.

(Contd. on page 3)

**Safety Data Sheet  
acc. to OSHA HCS**

Printing date 05/19/2015

Version 4

Reviewed on 05/19/2015

**Trade name: Polyken 1027 Liquid Adhesive**

(Contd. of page 2)

P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P240	Ground/bond container and receiving equipment.
P242	Use only non-sparking tools.
P273	Avoid release to the environment.
P243	Take precautionary measures against static discharge.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P321	Specific treatment (see on this label).
P304+P312	IF INHALED: Call a POISON CENTER/doctor if you feel unwell.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P331	Do NOT induce vomiting.
P370+P378	In case of fire: Use for extinction: CO2, powder or water spray.
P391	Collect spillage.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not available.
- **vPvB:** Not available.

**3 Composition/information on ingredients**

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

68410-97-9	Distillates (petroleum), light distillate hydrotreating process, low-boiling (note P) ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	50-100%
108-88-3	toluene ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	10-25%

(Contd. on page 4)

**Safety Data Sheet  
 acc. to OSHA HCS**

Printing date 05/19/2015

Version 4

Reviewed on 05/19/2015

**Trade name: Polyken 1027 Liquid Adhesive**

(Contd. of page 3)

67-56-1	methanol 	1.0-2.5%
1314-13-2	zinc oxide 	0.1-0.5%
140-66-9	4-(1,1,3,3-tetramethylbutyl)phenol 	≤ 0.1%

**4 First-aid measures**

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Immediately remove any clothing soiled by the product.

Personal protection for the First Aider.

· **After inhalation:**

Supply fresh air or oxygen; call for doctor.

Do not use mouth to mouth or mouth to nose resuscitation.

Use a respiration bag or breathing device.

Take affected persons into fresh air and keep quiet.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on his/her back should be turned onto his/her side.

Rinse out mouth and then drink plenty of water.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

- Asthma attacks
- Breathing difficulty
- Allergic reactions
- Dizziness
- Dizziness
- Unconsciousness
- Disorientation

· **Indication of any immediate medical attention and special treatment needed**

Medical supervision for at least 48 hours.

**5 Fire-fighting measures**

· **Extinguishing media**

· **Suitable extinguishing agents:**

Water haze

Foam

Fire-extinguishing powder

Carbon dioxide

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 5)

**Safety Data Sheet  
acc. to OSHA HCS**

Printing date 05/19/2015

Version 4

Reviewed on 05/19/2015

**Trade name: Polyken 1027 Liquid Adhesive**

(Contd. of page 4)

· **Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

· **Additional information**

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Disposal of fire debris and contaminated fire fighting water in accordance with official regulations.

## 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Mount respiratory protective device.

Keep away from ignition sources

Ensure adequate ventilation

· **Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to penetrate the ground/soil.

In case of seepage into the ground inform responsible authorities.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Ensure appropriate ventilation/exhaust at the workplace.

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Open and handle receptacle with care.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Prevent any seepage into the ground.

· **Information about storage in one common storage facility:**

Do not store together with acids.

Do not store together with alkalis (caustic solutions).

Store away from oxidizing agents.

Store away from reducing agents.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

(Contd. on page 6)

**Safety Data Sheet  
 acc. to OSHA HCS**

Printing date 05/19/2015

Version 4

Reviewed on 05/19/2015

**Trade name: Polyken 1027 Liquid Adhesive**

(Contd. of page 5)

Store receptacle in fume compartment.  
 Store under lock and key and out of the reach of children.

· **Specific end use(s)** No further relevant information available.

**8 Exposure controls/personal protection**

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**108-88-3 toluene**

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 75 mg/m <sup>3</sup> , 20 ppm BEI

**67-56-1 methanol**

PEL	Long-term value: 260 mg/m <sup>3</sup> , 200 ppm
REL	Short-term value: 325 mg/m <sup>3</sup> , 250 ppm Long-term value: 260 mg/m <sup>3</sup> , 200 ppm Skin
TLV	Short-term value: 328 mg/m <sup>3</sup> , 250 ppm Long-term value: 262 mg/m <sup>3</sup> , 200 ppm Skin; BEI

· **Ingredients with biological limit values:**

**108-88-3 toluene**

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

**67-56-1 methanol**

BEI	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
-----	---

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing.  
 Wash hands before breaks and at the end of work.  
 Store protective clothing separately.  
 Avoid contact with the eyes and skin.

(Contd. on page 7)

**Safety Data Sheet  
acc. to OSHA HCS**

Printing date 05/19/2015

Version 4

Reviewed on 05/19/2015

**Trade name: Polyken 1027 Liquid Adhesive**

(Contd. of page 6)

Do not inhale gases / fumes / aerosols.

Do not inhale dust / smoke / mist.

· **Breathing equipment:**

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use selfcontained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

**9 Physical and chemical properties**

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:**

Fluid

· **Color:**

Black

· **Odor:**

Petroleum-like

· **Odour threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

· **Melting point/Melting range:**

Undetermined.

· **Boiling point/Boiling range:**

> 118 °C (> 244 °F)

· **Flash point:**

10 °C (50 °F)

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

> 250 °C (> 482 °F)

· **Decomposition temperature:**

Not determined.

· **Auto igniting:**

Product is not selfigniting.

· **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

· **Lower:**

1.2 Vol %

(Contd. on page 8)

**Safety Data Sheet  
 acc. to OSHA HCS**

Printing date 05/19/2015

Version 4

Reviewed on 05/19/2015

**Trade name: Polyken 1027 Liquid Adhesive**

(Contd. of page 7)

· <b>Upper:</b>	7.0 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	29 hPa (22 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	0.84 g/cm <sup>3</sup> (7.01 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with</b>	
· <b>Water:</b>	Not miscible or difficult to mix.
· <b>Segregation coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
· <b>Dynamic:</b>	Not determined.
· <b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
· <b>Organic solvents:</b>	69.7 %
· <b>VOC:</b>	69.7 % 585.7 g/l / 4.89 lb/gl
· <b>Other information</b>	No further relevant information available.

**10 Stability and reactivity**

- **Reactivity**
  - **Chemical stability**
    - **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions**  
Reacts with acids, alkalis and oxidizing agents.  
Reacts with reducing agents.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:**  
Reacts with strong acids.  
Reacts with oxidizing agents.
- **Hazardous decomposition products:**  
Flammable gases/vapors  
Poisonous gases/vapors  
Carbon monoxide and carbon dioxide

**\* 11 Toxicological information**

- **Information on toxicological effects**
  - **Acute toxicity:**

· <b>LD/LC50 values that are relevant for classification:</b>		
<b>ATE (Acute Toxicity Estimates)</b>		
Inhalative	LC50/4h	217 mg/l
<b>68410-97-9 Distillates (petroleum), light distillate hydrotreating process, low-boiling (note P)</b>		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50	2.18 mg/l (air) (rat)
<b>108-88-3 toluene</b>		
Oral	LD50	>5000 mg/kg (rat)

(Contd. on page 9)



**Safety Data Sheet  
acc. to OSHA HCS**

Printing date 05/19/2015

Version 4

Reviewed on 05/19/2015

**Trade name: Polyken 1027 Liquid Adhesive**

(Contd. of page 8)

Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50/4h	28.1 mg/l (rat) (OECD 403)
<b>67-56-1 methanol</b>		
Oral	LD50	5628 mg/kg (rat)
Dermal	LD50	15800 mg/kg (rabbit)
Inhalative	LC50/4h	3 mg/l (ATE)
<b>1314-13-2 zinc oxide</b>		
Oral	LD50	> 5000 mg/kg (rat)
<b>140-66-9 4-(1,1,3,3-tetramethylbutyl)phenol</b>		
Oral	LD50	4040 mg/kg (rat) (OECD 401)
Dermal	LD50	>2000 mg/kg (rabbit) (OECD 402)

· **Primary irritant effect:**

- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:  
Harmful  
Carcinogenic.  
The product can cause inheritable damage.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**

· **Toxicity**

· **Aquatic toxicity:**

**68410-97-9 Distillates (petroleum), light distillate hydrotreating process, low-boiling (note P)**

EL50/48h	4.5 mg/l (Daphnia magna)
LL50/96h	8.2 mg/l (Fish - Pimephales promelas)
NOELR	0.5 mg/l (Algae - Pseudokirchnerella subcapitata)

**108-88-3 toluene**

LC50/48h	3.78 mg/l (Ceriodaphnia dubia) (US EPA 600/4-91-003)
LC50/96h	5.5 mg/l (Fish - Oncorhynchus kisutch) (Publ: Transactions A. Fish. Soc. 110, 430-43)

**1314-13-2 zinc oxide**

LC50/96h	330 mg/l (Fish - Pimephales promelas) (Literature - read across)
NOEC/72h	0.024 mg/l (Algae - Pseudokirchnerella subcapitata) (OECD 201)

**140-66-9 4-(1,1,3,3-tetramethylbutyl)phenol**

EC50/96h	1.9 mg/l (Algae - Pseudokirchnerella subcapitata) (EPA OPPTS 850.1020)
LC50/96h	0.26 mg/l (Fish - Leuciscus idus) (OECD 203)
	0.0196 mg/l (Gammarus pulex) (EPA OPPTS 850.1020)

· **Persistence and degradability** No further relevant information available.

(Contd. on page 10)

**Safety Data Sheet  
 acc. to OSHA HCS**

Printing date 05/19/2015

Version 4

Reviewed on 05/19/2015

**Trade name: Polyken 1027 Liquid Adhesive**



(Contd. of page 9)

- **Behavior in environmental systems:**
  - **Bioaccumulative potential** No further relevant information available.
  - **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
  - **General notes:**  
 Water hazard class 3 (Self-assessment): extremely hazardous for water  
 Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
 Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
  - **PBT:** Not available.
  - **vPvB:** Not available.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
  - **Recommendation:**  
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
  - **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

· <b>UN-Number</b>	
· <b>DOT, ADR, IMDG, IATA</b>	UN1133
· <b>UN proper shipping name</b>	
· <b>DOT</b>	Adhesives
· <b>ADR</b>	1133 Adhesives, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS
· <b>IMDG</b>	ADHESIVES (Distillates (petroleum), light distillate hydrotreating process, low-boiling (note P), zinc oxide), MARINE POLLUTANT
· <b>IATA</b>	ADHESIVES
· <b>Transport hazard class(es)</b>	
· <b>DOT</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>ADR, IMDG</b>	
	
· <b>Class</b>	3 Flammable liquids

(Contd. on page 11)

**Safety Data Sheet  
 acc. to OSHA HCS**


Printing date 05/19/2015

Version 4

Reviewed on 05/19/2015

**Trade name: Polyken 1027 Liquid Adhesive**

(Contd. of page 10)

· <b>Label</b>	3
· <b>IATA</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>Packing group</b>	
· <b>DOT, ADR, IMDG, IATA</b>	II
· <b>Environmental hazards:</b>	Product contains environmentally hazardous substances: zinc oxide, Distillates (petroleum), light distillate hydrotreating process, low-boiling (note P)
· <b>Marine pollutant:</b>	Yes (DOT) Symbol (fish and tree)
· <b>Special marking (ADR):</b>	Symbol (fish and tree)
· <b>Special precautions for user</b>	Warning: Flammable liquids
· <b>Danger code (Kemler):</b>	33
· <b>EMS Number:</b>	F-E,S-D
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· <b>Remarks:</b>	Special marking with the symbol (fish and tree).
· <b>ADR</b>	
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN1133, Adhesives, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS, 3, II

**\* 15 Regulatory information**

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
 · **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

108-88-3	toluene
67-56-1	methanol

(Contd. on page 12)

**Safety Data Sheet  
 acc. to OSHA HCS**

Printing date 05/19/2015

Version 4

Reviewed on 05/19/2015

**Trade name: Polyken 1027 Liquid Adhesive**

(Contd. of page 11)

1314-13-2	zinc oxide
1330-20-7	xylene
100-41-4	ethylbenzene

**· TSCA (Toxic Substances Control Act):**

All ingredients of this product are included, or are exempted from inclusion in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory

**· Proposition 65**

**· Chemicals known to cause cancer:**

100-41-4	ethylbenzene
----------	--------------

**· Chemicals known to cause reproductive toxicity for females:**

108-88-3	toluene
----------	---------

**· Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

**· Chemicals known to cause developmental toxicity:**

108-88-3	toluene
67-56-1	methanol

**· Carcinogenic categories**

**· EPA (Environmental Protection Agency)**

108-88-3	toluene	II
1314-13-2	zinc oxide	D, I, II
1330-20-7	xylene	I
100-41-4	ethylbenzene	D

**· TLV (Threshold Limit Value established by ACGIH)**

108-88-3	toluene	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3

**· NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

**· GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

**· Hazard pictograms**



**· Signal word** Danger

**· Hazard-determining components of labeling:**

Distillates (petroleum), light distillate hydrotreating process, low-boiling (note P)  
 toluene  
 methanol

**· Hazard statements**

H225 Highly flammable liquid and vapor.  
 H315 Causes skin irritation.  
 H361 Suspected of damaging fertility or the unborn child.  
 H336 May cause drowsiness or dizziness.  
 H373 May cause damage to the central nervous system through prolonged or repeated exposure.  
 H304 May be fatal if swallowed and enters airways.  
 H411 Toxic to aquatic life with long lasting effects.

**· Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 13)

**Safety Data Sheet  
acc. to OSHA HCS**

Printing date 05/19/2015

Version 4

Reviewed on 05/19/2015

**Trade name: Polyken 1027 Liquid Adhesive**

(Contd. of page 12)

P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P240	Ground/bond container and receiving equipment.
P242	Use only non-sparking tools.
P273	Avoid release to the environment.
P243	Take precautionary measures against static discharge.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P321	Specific treatment (see on this label).
P304+P312	IF INHALED: Call a POISON CENTER/doctor if you feel unwell.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P331	Do NOT induce vomiting.
P370+P378	In case of fire: Use for extinction: CO2, powder or water spray.
P391	Collect spillage.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Occupational product safety department of Seal For Life Industries

· **Contact:**

Seal For Life Industries  
Gasselterstraat 20, 9503JB Stadskanaal, the Netherlands  
Tel: +31 599 696 170; Fax: +31 599 696 177; Email: info@sealforlife.com

· **Date of preparation / last revision** 05/19/2015 / 3

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
ACGIH: American Conference of Governmental Industrial Hygienists  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
Flam. Liq. 2: Flammable liquids, Hazard Category 2  
Acute Tox. 3: Acute toxicity, Hazard Category 3  
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2  
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1  
Repr. 2: Reproductive toxicity, Hazard Category 2  
STOT SE 1: Specific target organ toxicity - Single exposure, Hazard Category 1  
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3  
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2  
Asp. Tox. 1: Aspiration hazard, Hazard Category 1  
Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

(Contd. on page 14)

**Safety Data Sheet  
acc. to OSHA HCS**

Printing date 05/19/2015

Version 4

Reviewed on 05/19/2015

---

**Trade name: Polyken 1027 Liquid Adhesive**

---

(Contd. of page 13)

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

· \* **Data compared to the previous version altered.**

---

— US —