

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION
PRODUCT NAME: Christy's Red Hot Vinyl Construction Adhesive - Fast & Slow

PRODUCT USE: 2-Component acrylic-based adhesive for bonding cellular PVC trim and moldings.

SUPPLIER:
MANUFACTURER: Weld-On Adhesives, Inc.
 17109 S Main Street
 Gardena, CA 90248
 (800) 888-8312

EMERGENCY: Transportation: CHEMTEL Tel. 800-255-3924, +1 813-248-0585 (International) **Medical:** CHEMTEL Tel. 800-255-3924, +1 813-248-0585 (International)

SECTION 2 - HAZARDS IDENTIFICATION
GHS CLASSIFICATION:

Acute Toxicity:	Health Category 4	Acute Toxicity:	Environmental Category III	Flammable Liquid:	Physical Category 2
Skin Irritation:	Category 3	Chronic Toxicity:	Category IV		
Skin Sensitization:	YES				
Eye:	Category 2B				

GHS LABEL:

Signal Word:
Danger
WHMIS CLASSIFICATION: CLASS B, DIVISION 2
 CONTROLLED PRODUCT CLASS D, DIVISION 2B

Hazard Statements

 H225: Highly flammable liquid and vapour.
 H315: Causes skin irritation.
 H317: May cause an allergic skin reaction.
 H335: May cause respiratory irritation.

Precautionary Statements

 P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P233: Keep container tightly closed.
 P261: Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
 P403: Store in a well-ventilated place.
 P501: Dispose of contents/container in accordance with local regulation

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

	CAS #	EINECS #	REACH	CONCENTRATION
			Pre-registration Number	% by Weight
Component "A" (White-Adhesive)				
Methyl Methacrylate Monomer (MMA),* Stabilized	80-62-6	201-297-1	05-2116297731-37-0000	40 - 60
Methacrylic Acid (MAA)	79-41-4	201-204-4	05-2116297727-26-0000	5 - 15
Butylated Hydroxytoluene	128-37-0	204-881-4	01-2119565113-46-XXXX	0 - 5
Cumyl Hydroperoxide	80-15-9	201-254-7	Not Registered	0 - 5
Titanium Dioxide	13463-67-7	236-675-5	Under Review	1 - 15
Silicon Dioxide	67762-90-7	614-122-2	Under Review	0 - 5
Component "B" (Beige-Activator)				
Methyl Methacrylate Monomer (MMA),* Stabilized	80-62-6	201-297-1	05-2116297731-37-0000	40 - 60
Trimethylolpropane Trimethacrylate	3290-92-4	221-950-4	Under Review	1 - 15
3,5-Diethyl-1,2-dihydro-1-phenyl-2-propylpyridine	34562-31-7	252-091-3	Not Registered	0 - 5

All of the constituents of this adhesive product are listed on the TSCA inventory of chemical substances maintained by the US EPA, or are exempt from that listing.
 *Indicates this chemical is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (40CFR372).
 # indicates that this chemical is found on Proposition 65's List of chemicals known to the State of California to cause cancer or reproductive toxicity.

SECTION 4 - FIRST AID MEASURES

Contact with eyes: Flush eyes immediately with plenty of water for 15 minutes and seek medical advice immediately.
Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water. If irritation develops, seek medical advice.
Inhalation: Move to fresh air. If breathing is stopped, give artificial respiration. If breathing is difficult, give oxygen. Seek medical advice.
Ingestion: Rinse mouth with water. Give 1 or 2 glasses of water or milk to dilute. Do not induce vomiting. Seek medical advice immediately.

Likely Routes of Exposure: Inhalation, Eye and Skin Contact

Acute symptoms and effects:

Inhalation: Severe overexposure may result in nausea, dizziness, headache. Can cause drowsiness, irritation of eyes and nasal passages.
Eye Contact: Vapors slightly uncomfortable. Overexposure may result in severe eye injury with corneal or conjunctival inflammation on contact with the liquid.
Skin Contact: Liquid contact may remove natural skin oils resulting in skin irritation. Dermatitis may occur with prolonged contact.
Ingestion: May cause nausea, vomiting, diarrhea and mental sluggishness.

Chronic (long-term) effects(MMA): Toxic to lungs, mucous membranes. Repeated or prolonged exposure to the substance can produce target organs damage.

SECTION 5 - FIREFIGHTING MEASURES

Suitable Extinguishing Media:	Dry chemical powder, carbon dioxide gas, foam, Halon, water fog.	HMIS	NFPA	0-Minimal
Unsuitable Extinguishing Media:	Water spray or stream.	Health	2	2
Exposure Hazards:	Inhalation and dermal contact	Flammability	3	3
Combustion Products:	Oxides of carbon, oxides of nitrogen, hydrocarbons, acrid smoke and gases	Reactivity	2	2
Protection for Firefighters:	Self-contained breathing apparatus or full-face positive pressure air-supply masks.			4-Severe

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions: Keep away from heat, sparks and open flame.
 Provide sufficient ventilation, use explosion-proof exhaust ventilation equipment or wear suitable respiratory protective equipment.
 Prevent contact with skin or eyes (see section 8).
Environmental Precautions: Prevent product or liquids contaminated with product from entering sewers, drains, soil or open water course.
Methods for Cleaning up: Sand or other inert absorbent material. Use non-sparking tools. Transfer to a closable vessel (Metal or polyethylene (PE))

SECTION 7 - HANDLING AND STORAGE

Handling: Avoid breathing of vapor, avoid contact with eyes, skin and clothing.
 Keep away from ignition sources, use only electrically grounded handling equipment and ensure adequate ventilation/fume exhaust hoods.
 Do not eat, drink or smoke while handling.
Storage: Store in ventilated room or shade and away from direct sunlight. Keep container tightly closed when not in use.
 Keep away from ignition sources and incompatible materials. Follow all precautionary information on container label and product bulletins.

SECTION 8 - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:	Component	ACGIH	ACGIH	OSHA	OSHA	OSHA	CAL/OSHA	CAL/OSHA	CAL/OSHA
		8hr-TLV	15min- STEL	8hr-PEL	15min- STEL	Ceiling	8hr-PEL	15min- STEL	Ceiling
	Methyl Methacrylate Mon.	50 ppm	100 ppm	100 ppm	N/E	N/E	50 ppm	100 ppm	N/E
	Methacrylic Acid	20 ppm skin	N/E	20 ppm skin	N/E	N/E	20 ppm skin	N/E	N/E

Engineering Controls: Use local exhaust as needed.

Monitoring: Maintain breathing zone airborne concentrations below exposure limits.

Personal Protective Equipment (PPE):

Eye Protection: Avoid contact with eyes, wear splashproof chemical goggles, face shield, safety glasses (spectacles) with brow guards and side shields,
Skin Protection: Prevent contact with the skin as much as possible. Butyl rubber gloves should be used for frequent immersion.
 Use of solvent-resistant gloves or solvent-resistant barrier cream should provide adequate protection when normal adhesive application practices and procedures are used for making structural bonds.

Respiratory Protection: Use in a well-ventilated room. Use local exhaust ventilation to remove airborne contaminants from employee breathing zone and to keep contaminants below levels listed above. With normal use, the Exposure Limit Value will not usually be reached. When limits are approached, use respiratory protection equipment.



GHS SAFETY DATA SHEET

Christy's Red Hot Vinyl Construction Adhesive - Fast & Slow Two-Component 1:1 Ratio Cartridge - White

Date Revised: April 2021
Supersedes: new

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	"A" - White, viscous paste, "B" - Biege, viscous paste	Odor Threshold:	"A & B" - 0.75 ppm: MMA
Odor:	"A & B" - Strong Solvent Odor	Active Oxygen Content:	N/A
pH:	Not Applicable	Evaporation Rate:	"A & B" - > 1.0 based on MMA (BUAC = 1)
Boiling Point:	"A & B" -100.5°C (212.9°F) Based on first boiling component: MMA	Flammability:	"A & B" - Category 2
Flash Point:	"A & B" - 11.5°C (52.7°F) T.C.C. based on MMA	Flammability Limits:	LEL: "A & B" - 1.6% based on MMA UEL: "A & B" - 12.5% based on MMA
Specific Gravity:	"A & B" - 1.140 +/- 0.02 @ 73F +/- 2	Vapor Pressure:	"A & B" - 28 mm Hg @ 20°C (68°F): MMA
Solubility:	"A & B" - Slight in Water (MMA, MAA)	Vapor Density:	"A & B" - > 3.0 (Air = 1) based on MMA
Auto-ignition Temperature:	"A & B" - 421°C (789.8°F): MMA	VOC Content:	"A" - ≤ 50 g/l mixed, based on MMA
Decomposition Temperature:	"A & B" - Not Applicable based on MMA		

SECTION 10 - STABILITY AND REACTIVITY

Stability:	Stable, unless heated
Hazardous decomposition products:	None in normal use. Oxides of carbon, oxides of nitrogen, hydrocarbons, acrid smoke and gases.
Conditions to avoid:	Keep away from direct sunlight, heat, sparks, open flame and other ignition sources.
Incompatible Materials:	Reducing and oxidizing agents and metal contaminants

SECTION 11 - TOXICOLOGICAL INFORMATION

Toxicity:	LD50	LC50
Methyl Methacrylate Monomer (MMA)	Oral: 7900 mg/kg (rat), Dermal: >35000 mg/kg (rabbit)	Inhalation: 3 hrs. 7093 PPM (rat)
Methacrylic Acid	Oral: 1600 mg/kg (rat), Dermal: 500 mg/kg (rabbit)	Inhalation: 6.7 mg/l (rat)

Reproductive Effects	Teratogenicity	Mutagenicity	Embryotoxicity	Sensitization to Product	Synergistic Products
Not Established	Not Established	Not Established	Not Established	Not Established	Not Established

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: MMA	Species	Test Results
	Toxicity to fish	LC50-Pimephales promelas (fathead minnow) 125.5 - 275.0 mg/l - 96 h
	Toxicity to daphnia	EC50 WaterFlea (Daphnia magna) 720 mg/l
	Toxicity to algae	EC50 - P. subcapitata (green algae) 170 mg/l - 96 h
Mobility:	In normal use, emission of volatile organic compounds (VOC's) to the air takes place, typically at a rate of ≤ 50 g/l	
Degradability:	Not Established	
Bioaccumulation:	Not Established	

SECTION 13 - WASTE DISPOSAL CONSIDERATIONS

Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contact your supplier or a licensed contractor for detailed recommendations. Do not re-use empty containers.

SECTION 14 - TRANSPORT INFORMATION

Proper Shipping Name:	Adhesives
Hazard Class:	3
Secondary Risk:	None
Identification Number:	UN 1133
Packing Group:	PG II
Label Required:	Class 3 Flammable Liquid
Marine Pollutant:	NO

EXCEPTION for Ground Shipping

DOT Limited Quantity: Up to 5L per inner packaging, 30 kg gross weight per package.
Consumer Commodity: Depending on packaging, these quantities may qualify under DOT as "ORM-D".

TDG INFORMATION

TDG CLASS:	FLAMMABLE LIQUID 3
SHIPPING NAME:	ADHESIVES
UN NUMBER/PACKING GROUP:	UN 1133, PG II

SECTION 15 - REGULATORY INFORMATION

Precautionary Label Information:	Highly Flammable, Harmful	Ingredient Listings:	USA TSCA, Europe EINECS, Canada DSL, Australia AICS, Korea ECL/TCCL, Japan MITI (ENCS)
Symbols:	F, Xn		
Risk Phrases:	R-11 Highly Flammable R-20 Harmful by inhalation R-21 Harmful if contact with skin R-22 Harmful if swallowed	R-36/37/38 Irritating to eyes, respiratory system and skin R-43 May cause sensitization by skin contact.	
Safety Phrases:	S-2 Keep out of reach of children S-7 Keep container tightly closed when not in use S-9 Keep container in a well-ventilated place S-15/16 Keep away from heat and sources of ignition. No smoking S-23 Do not breathe vapor	S-24/25 Avoid contact with skin and eyes. S-29 Do not empty into drains S-37 Wear suitable gloves S-51 Use only in well ventilated areas	

SECTION 16 - OTHER INFORMATION

Specification Information:		
Department issuing data sheet:	IPS, Safety Health & Environmental Affairs	All ingredients are compliant with the requirements of the European Directive on RoHS (Restriction of Hazardous Substances).
E-mail address:	<EHSinfo@ipscorp.com>	
Training necessary:	Yes, training in practices and procedures contained in product literature.	
Reissue date / reason for reissue:	4/5/2021 Updated GHS Standard Format	
Intended Use of Product:	2-Component Adhesive for bonding thermoplastics, metals and other composites	

This product is intended for use by skilled individuals at their own risk. The information contained herein is based on data considered accurate based on current state of knowledge and experience. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.