



PRIME-IT!

Christy's® PRIME-IT! is a light amber, medium bodied, rubber-based, special purpose contact adhesive for bonding a variety of porous and non-porous surfaces.

- A pro-grade, high tack, fast drying special purpose contact adhesive formulated for bonding pipe wrap tape to pipe.
- Suitable for bonding drainpipe, foam, fabric, glass, leather, metal, wood, and plastic.
- Professionally bonds porous and non-porous surfaces. Easy to penetrate pitted and irregular surfaces.
- Low VOC

Prime-It! is not a solvent cement and does not solvent weld plastic. Refer to Christy's line of solvent cement for solvent-welding plastic pipe systems.

PRODUCT SPECIFICATIONS

Pipe Type	Metal or Plastic
Uses	Special purpose contact adhesive for securing pipe wrap tape to metal or plastic pipe. Also bond plastic, rubber, glass, metal and leather.
Color	Light Amber
Relative Set Time	Fast Set
Body	Medium Bodied
Brookfield Viscosity	Minimum 1,200 cps
Specific Gravity	0.847 ± 0.04
VOC Emissions	212 g/L
Shelf Life	3 Years
LEED Compliant	Credit can be earned per LEED® (Leadership in Energy and Environmental Design), IEQ Credit 4.1

SPECIAL PRECAUTION

Christy's solvent products must never be used in plastic piping system using or being tested by compressed air or gases; including air-over-water booster. Do not use in conjunction with flue gas ventilation systems.

Do not use a dry granular calcium hypochlorite as a disinfecting material for water purification in potable water piping systems. The introduction of granules or pellets of calcium hypochlorite with solvent cements and primers (including their vapors) may result in a violent chemical reaction if a water solution is not used. It is advisable to purify lines by pumping chlorinated water into the piping system – this solution will be nonvolatile. Furthermore, dry granular calcium hypochlorite should not be stored or used near solvent cements and primers.

This product is intended for use by skilled individuals at their own risk. Installers should verify for themselves that they can make satisfactory joints under varying conditions. Detailed directions on making solvent cemented joints are printed on the container label. It is highly recommended that the installer review the instructions supplied by the pipe and fitting manufacturer.

Refer to the current Safety Data Sheet for additional safety precautions, first-aid, storage, handling, transportation and disposal information.

Storage temperature: 40°F (5°C) – 110°F (43°C)

Refer to website for complete Terms and Conditions.