





PRODUCT SPECIFICATIONS

Pipe Type	PVC, Schedule 40 & 80
Cement Uses:	For PVC pipe and fitting applications; potable water, pressure, non-pressure, conduit, drain, DWV, and sewer
Maximum Diameter	For PVC pipe sizes thru 6" (150mm) all schedules and classes. Schedule 80 thru 4" (100mm)
Color	Clear
Relative Set Time	Fast Set
Body	Medium Body
Performance Specification	ASTM D-2564, NSF/ANSI 14, NSF/ANSI 61, NSF/ANSI 372
Brookfield Viscosity	Minimum 500 cP @73°F +/- 2°F 23°C +/- 1°C
Specific Gravity	Typical 0.963 +/- 0.04
Industry Listing	 U.P. Code PW-DWV-SW
Max VOC Emissions	510 g/l per SCAQMD Rule 1168 Method 316A 
Shelf Life	3 Years
LEED Compliant	Low VOC formulation can earn credit toward the U.S. Green Building Council's LEED certification for green buildings. 

CLEAR MEDIUM BODY PVC CEMENT

Christy's **CLEAR MEDIUM BODY PVC CEMENT** is an professional grade, medium bodied, fast setting, high strength PVC solvent cement. Can be used in plumbing, industrial, irrigation, agricultural, municipal, or pool and spa applications including PVC foam core.

- Professional grade, high strength PVC cement specially formulated to join pipe and fitting surfaces and create a strong quick bond
- Medium body formulation delivers good gap filling capacity between pipe & fittings
- Clear formulation for clean joints in exposed installations
- For all classes and schedules of PVC pipe thru 6" (150mm). For use on Schedule 80 thru 4" (100mm)
- For PVC pipe and fitting applications; potable water, pressure, non-pressure, conduit, drain, duct, DWV and sewer
- Low VOC

CASE PACK CONFIGURATIONS

Item #	Can Size	Cans/Cs	Can UPC
RH-MCLV-QP-24	¼ Pint, 4 oz (118 ml)	24	044752335775
RH-MCLV-HP-24	½ Pint, 8 oz (237 ml)	24	044752335751
RH-MCLV-PT-12	Pint, 16 oz (473 ml)	12	044752335768
RH-MCLV-QT-12	Quart, 32 oz (946 ml)	12	044752335782
RH-MCLV-GL-6	Gallon, 128 oz (3.785 l)	6	044752335744

SPECIAL CONSIDERATIONS: Consult the SDS for health and safety specifics. Always use in a well-ventilated environment. Wear safety glasses and gloves at all times. DO NOT USE a dry granular calcium hypochlorite as a disinfecting material for water purification in potable water piping systems. The introduction of granules or pellets of calcium hypochlorite with PVC and CPVC solvent cements and primers (including their vapors) may result in a violent chemical reaction if a water solution is not used. It is advisable to purify lines by pumping chlorinated water into the piping system - this solution will be non-volatile. Furthermore, dry granular calcium hypochlorite should not be stored or used near solvent cements and primers.

THIS PRODUCT IS NOT FOR USE IN A SYSTEM USING OR BEING TESTED WITH COMPRESSED AIR OR GASSES.

T. Christy Enterprises, Inc.



655 E. Ball Rd. • Anaheim, CA 92805

Tel: (714) 507-3300 • Fax: (714) 507-3310

www.TChristy.com • 800-BLU-GLUE