





PRODUCT SPECIFICATIONS	
Pipe Type	PVC, Schedule 40 & 80
Cement Uses:	For PVC pipe and fitting applications; potable water, pressure, non-pressure, conduit, drain, DWV, and sewer
Maximum Diameter	For pipe sizes with interference fit thru 30" (750mm) all classes and schedules.
Color	White
Relative Set Time	Slow Set
Body	Extra Heavy Body
Performance Specification	ASTM D-2564, NSF/ANSI 14, NSF/ANSI 61, NSF/ANSI 372
Brookfield Viscosity	Minimum 200,000 cP @73°F +/- 2°F 23°C +/- 1°C
Specific Gravity	Typical 0.984 +/- 0.04
Industry Listing	 U.P. Code PW-DWV-SW
Max VOC Emissions	510 g/l per SCAQMD Rule 1168 Method 316A 
Shelf Life	3 Years
LEED Compliant	Low VOC formulation can earn credit toward the U.S. Green Building Council's LEED certification for green buildings. 

## EXTRA HEAVY WHITE PVC CEMENT

Christy's **EXTRA HEAVY WHITE PVC PIPE CEMENT** is an industrial grade, extra heavy body, slow setting, high strength PVC cement for large diameter applications or where more working time is required. For use in agricultural, municipal, irrigation, industrial and plumbing applications.

- **Industrial grade, extra heavy body high strength PVC cement for large diameter applications where more working time is required. Also recommended for hot weather applications**
- **Extra Heavy Body formulation delivers superior gap filling capacity between pipe & fittings**
- **White color enables visual confirmation that cement has been applied**
- **For pipe sizes with interference fit thru 30" (750mm) all classes and schedules**
- **For PVC pipe and fitting applications; potable water, pressure, non-pressure, conduit, drain, duct, DWV and sewer**
- **Low VOC**

CASE PACK CONFIGURATIONS			
Item #	Can Size	Cans/Cs	Can UPC
RH-WXHD-PT-12	Pint, 16 oz (473 ml)	12	044752338431
RH-WXHD-QT-12	Quart, 32 oz (946 ml)	12	044752338424
RH-WXHD-GL-4	Gallon, 128 oz (3.785 l)	4	044752338417
RH-WXHD-5GL	5 Gallon, 640 oz (18.93 l)	1	044752334807

**SPECIAL CONSIDERATIONS:** Consult the SDS for health and safety specifics. Always use in a well-ventilated environment. Wear safety glasses and gloves at all times. **DO NOT USE** a dry granular calcium hypochlorite as a disinfecting material for water purification in potable water piping systems. The introduction of granules or pellets of calcium hypochlorite with PVC and CPVC solvent cements and primers (including their vapors) may result in a violent chemical reaction if a water solution is not used. It is advisable to purify lines by pumping chlorinated water into the piping system - this solution will be non-volatile. Furthermore, dry granular calcium hypochlorite should not be stored or used near solvent cements and primers.

**THIS PRODUCT IS NOT FOR USE IN A SYSTEM USING OR  
BEING TESTED WITH COMPRESSED AIR OR GASSES.**



T. Christy Enterprises, Inc.

655 E. Ball Rd. • Anaheim, CA 92805

Tel: (714) 507-3300 • Fax: (714) 507-3310

www.TChristy.com • 800-BLU-GLUE