



## PRODUCT SPECIFICATIONS

Pipe Type	PVC, Schedule 40 & 80
Cement Uses:	For pool, spa, water gardening, irrigation and other applications
Maximum Diameter	For PVC pipe sizes thru 6" (150 mm) all schedules and classes, Schedule 80 thru 4" (100 mm)
Color	Clear
Relative Set Time	Fast Set
Body	Medium Body
Performance Specification	ASTM D-2564, NSF/ANSI 14, NSF/ANSI 61, NSF/ANSI 372
Brookfield Viscosity	Minimum 500 cP @73°F +/- 2°F 23°C +/- 1°C
Specific Gravity	Typical 0.94 +/- 0.04
Industry Listing	 U.P. Code PW-DWV-SW
Max VOC Emissions	510 g/l per SCAQMD Rule 1168 Method 316A 
Shelf Life	3 Years
LEED Compliant	Low VOC formulation can earn credit toward the U.S. Green Building Council's LEED certification for green buildings. 

## Flex Pro PVC Pipe Cement

Preferred for use with flexible PVC piping

Working with flexible PVC pipe? Reach for a solvent cement that's specially formulated for the unique challenges of flexible joints, Christy's Flex Pro. Flex Pro is used for pool, spa, water gardening, irrigation and other applications. It forms flexible, high-strength water resistant joints in both flex-to-flex and flex-to-fitting applications.

- High performance solvent cement specially formulated to work with unique challenges of flexible joints
- Will form flexible, high-strength water resistant joints in both flex-to-flex and flex-to-fitting applications
- Uniquely resilient to vibrations common with spa and swimming pool installations
- For use on flexible risers and drop lines in irrigation
- For pool, spa, water gardening, irrigation and other applications
- Low VOC

## CASE PACK CONFIGURATIONS

Item #	Can Size	Cans/Cs	Can UPC
RH-FLEX-QP-24	¼ Pint, 4 oz (118 ml)	24	044752339476
RH-FLEX-HP-24	½ Pint, 8 oz (237 ml)	24	044752339452
RH-FLEX-PT-12	Pint, 16 oz (473 ml)	12	044752339469
RH-FLEX-QT-12	Quart, 32 oz (946 ml)	12	044752339483
RH-FLEX-GL-6	Gallon, 128 oz (3.785 l)	6	044752339445

**SPECIAL CONSIDERATIONS:** Consult the SDS for health and safety specifics. Always use in a well-ventilated environment. Wear safety glasses and gloves at all times. DO NOT USE a dry granular calcium hypochlorite as a disinfecting material for water purification in potable water piping systems. The introduction of granules or pellets of calcium hypochlorite with PVC and CPVC solvent cements and primers (including their vapors) may result in a violent chemical reaction if a water solution is not used. It is advisable to purify lines by pumping chlorinated water into the piping system - this solution will be non-volatile. Furthermore, dry granular calcium hypochlorite should not be stored or used near solvent cements and primers.

T. Christy Enterprises, Inc.



655 E. Ball Rd. • Anaheim, CA 92805

Tel: (714) 507-3300 • Fax: (714) 507-3310

www.TChristy.com • 800-BLU-GLUE

**THIS PRODUCT IS NOT FOR USE IN A SYSTEM USING OR BEING TESTED WITH COMPRESSED AIR OR GASSES.**