






PRODUCT SPECIFICATIONS

Pipe Type	PVC, Schedule 40 only
Cement Uses:	For PVC pipe and fitting applications; potable water, pressure, non-pressure, conduit, drain, duct, DWV and sewer excluding Sch. 80
Maximum Diameter	For PVC pipe sizes thru 4" (100mm) all schedules and classes. Not for Sch. 80
Color	PVC Cement: Clear Primer: Purple
Relative Set Time	PVC Cement: Fast Set
Body	PVC Cement: Regular Body
Performance Specification	PVC Cement: ASTM D-2564, Primer: ASTM F-656, NSF/ANSI 14, NSF/ANSI 61, NSF/ANSI 372
Brookfield Viscosity	PVC Cement: Minimum 90 cP Primer: Water Thin @73°F +/- 2°F @23°C +/- 1°C
Specific Gravity	Typical PVC Cement: 0.924 +/- 0.04 Primer 0.842 +/- 0.04
Industry Listing	 U.P. Code PW-DWV-SW
Max VOC Emissions	PVC Cement: 510 g/l Primer: 550 g/l per SCAQMD Rule 1168 Method 316A 
Shelf Life	3 Years
LEED Compliant	Low VOC formulation can earn credit toward the U.S. Green Building Council's LEED certification for green buildings. 

T. Christy Enterprises, Inc.



655 E. Ball Rd. • Anaheim, CA 92805

Tel: (714) 507-3300 • Fax: (714) 507-3310

www.TChristy.com • 800-BLU-GLUE

HANDY PACK

CLEAR REGULAR BODY PVC CEMENT & PURPLE PRIMER

Christy's Clear Regular Body PVC Cement and Purple Primer Handy Pack is a convenient package of professional-grade, high-strength cement and primer specially formulated to tackle demanding PVC solvent welding projects. Christy's all-in-one Handy Pack includes what you need to get the job done quickly and with less waste.

- A convenient package just add PVC pipe and fittings to get a professional, fast installation
- Includes 1 can each of Clear Regular PVC Cement and Purple Primer, 8 oz.
- Purple Primer is a professional grade, aggressive primer used to soften PVC and CPVC pipe and fitting surfaces
- Clear Regular PVC cement is a professional grade, high strength PVC cement specially formulated to bond small diameter pipe and fittings thru 4" (100mm), excluding Sch. 80
- For PVC pipe and fitting applications; potable water, pressure, non-pressure, conduit, drain, duct, DWV and sewer, excluding Sch. 80

CASE PACK CONFIGURATIONS

Item #	Can Size	Cans/Cs	Can UPC
RH-RLV-HDYPK-HP-20	½ Pint, 8 oz (237 ml)	20	044752338356

SPECIAL CONSIDERATIONS: Consult the SDS for health and safety specifics. Always use in a well-ventilated environment. Wear safety glasses and gloves at all times. DO NOT USE a dry granular calcium hypochlorite as a disinfecting material for water purification in potable water piping systems. The introduction of granules or pellets of calcium hypochlorite with PVC and CPVC solvent cements and primers (including their vapors) may result in a violent chemical reaction if a water solution is not used. It is advisable to purify lines by pumping chlorinated water into the piping system - this solution will be non-volatile. Furthermore, dry granular calcium hypochlorite should not be stored or used near solvent cements and primers.

**THIS PRODUCT IS NOT FOR USE IN A SYSTEM USING OR
BEING TESTED WITH COMPRESSED AIR OR GASSES.**