



PRODUCT SPECIFICATIONS

Pipe Type	PVC, Schedule 40 & 80
Cement Uses:	For PVC pipe and fitting applications; potable water, pressure, non-pressure, conduit, drain, duct, DWV and sewer
Maximum Diameter	For PVC pipe sizes thru 6" (150mm) all schedules and classes. Schedule 80 thru 4" (100mm)
Color	PVC Cement: Deep Blue Primer: Purple
Relative Set Time	PVC Cement: Very Fast Set
Body	PVC Cement: Medium Body
Performance Specification	PVC Cement: ASTM D-2564, Primer: ASTM F-656, NSF/ANSI 14, NSF/ANSI 61, NSF/ANSI 372
Brookfield Viscosity	PVC Cement: Minimum 500 cP Primer: Water Thin @73°F +/- 2°F @23°C +/- 1°C
Specific Gravity	Typical PVC Cement: 0.955 +/- 0.04 Primer 0.842 +/- 0.04
Industry Listing	 U.P. Code PW-DWV-SW
Max VOC Emissions	PVC Cement: 510 g/l Primer: 550 g/l per SCAQMD Rule 1168 Method 316A 
Shelf Life	3 Years
LEED Compliant	Low VOC formulation can earn credit toward the U.S. Green Building Council's LEED certification for green buildings. 

HANDY PACK RED HOT BLUE GLUE® & PURPLE PRIMER

Christy's Red Hot Blue Glue® and Purple Primer Handy Pack is a convenient package of professional-grade, high-strength cement and primer specially formulated to tackle demanding PVC solvent welding projects. Christy's all-in-one Handy Pack includes what you need to get the job done quickly and with less waste.

- A convenient package just add PVC pipe and fittings to get a professional, fast installation
- Includes 1 can each of "contractor preferred" Red Hot Blue Glue® and Purple Primer, 8 oz.
- Red Hot Blue Glue is "The Original" Blue Glue that quickly bonds PVC pipe & fittings for fast pressurization and maximum productivity
- Purple Primer is a professional grade, aggressive primer used to soften PVC and CPVC pipe and fitting surfaces
- For PVC pipe and fitting applications; potable water, pressure, non-pressure, conduit, drain, duct, DWV and sewer
- Low VOC

CASE PACK CONFIGURATIONS

Item #	Can Size	Cans/Cs	Can UPC
RH-RHBV-HDYPK-HP-20	½ Pint, 8 oz (237 ml)	20	044752342803

SPECIAL CONSIDERATIONS: Consult the SDS for health and safety specifics. Always use in a well-ventilated environment. Wear safety glasses and gloves at all times. DO NOT USE a dry granular calcium hypochlorite as a disinfecting material for water purification in potable water piping systems. The introduction of granules or pellets of calcium hypochlorite with PVC and CPVC solvent cements and primers (including their vapors) may result in a violent chemical reaction if a water solution is not used. It is advisable to purify lines by pumping chlorinated water into the piping system - this solution will be non-volatile. Furthermore, dry granular calcium hypochlorite should not be stored or used near solvent cements and primers.

**THIS PRODUCT IS NOT FOR USE IN A SYSTEM USING OR
BEING TESTED WITH COMPRESSED AIR OR GASSES.**

T. Christy Enterprises, Inc.



655 E. Ball Rd. • Anaheim, CA 92805

Tel: (714) 507-3300 • Fax: (714) 507-3310

www.TChristy.com • 800-BLU-GLUE