



PRODUCT SPECIFICATIONS

Pipe Type	PVC, Schedule 40 & 80
Cement Uses:	For PVC pipe and fitting applications; pool & spa, potable water, pressure, non-pressure, conduit, drain, duct, DWV and sewer
Maximum Diameter	For PVC pipe sizes thru 6" (150 mm) all schedules and classes, Schedule 80 thru 4" (100 mm)
Color	Blue Fade to Clear
Relative Set Time	Very Fast Set
Body	Medium Body
Performance Specification	ASTM D-2564, NSF/ANSI 14, NSF/ANSI 61, NSF/ANSI 372
Brookfield Viscosity	Minimum 500 cP @73°F +/- 2°F @23°C +/- 1°C
Specific Gravity	Typical 0.924 +/- 0.04
Industry Listing	 U.P. Code PW-DWV-SW
Max VOC Emissions	510 g/l per SCAQMD Rule 1168 Method 316A 
Shelf Life	3 Years
LEED Compliant	Low VOC formulation can earn credit toward the U.S. Green Building Council's LEED certification for green buildings. 

RED HOT POOL PRO™ PVC PIPE CEMENT

High-performance PVC solvent cement for pool/spa applications

Christy's RED HOT POOL PRO is high-performance solvent cement for joining PVC pipe and fittings in pool, spa, and whirlpool applications.

- **Designed for Pool & Spa Applications.** High quality, low drip formula that fades to clear after exposure to sunlight for clean joints in exposed installations
- **A thick, medium body cement.** Grips pipe & fittings fast with fewer drips. Very fast set
- **Initial blue color enables visual confirmation** that cement has been applied
- **For PVC pipe sizes thru 6" (150 mm) all schedules and classes.** Schedule 80 thru 4" (100 mm)
- **For PVC pipe and fitting applications; pool & spa, potable water, pressure, non-pressure, conduit, drain, duct, DWV and sewer**
- **Low VOC**

CASE PACK CONFIGURATIONS

Item #	Can Size	Cans/Cs	Can UPC
RH-POOL-QP-24	¼ Pint, 4 oz (118 ml)	24	044752336482
RH-POOL-HP-24	½ Pint, 8 oz (237 ml)	24	044752336505
RH-POOL-PT-12	Pint, 16 oz (473 ml)	12	044752336499
RH-POOL-QT-12	Quart, 32 oz (946 ml)	12	044752336475
RH-POOL-GL-6	Gallon, 128 oz (3.785 l)	6	044752336512

SPECIAL CONSIDERATIONS: Consult the SDS for health and safety specifics. Always use in a well-ventilated environment. Wear safety glasses and gloves at all times. DO NOT USE a dry granular calcium hypochlorite as a disinfecting material for water purification in potable water piping systems. The introduction of granules or pellets of calcium hypochlorite with PVC and CPVC solvent cements and primers (including their vapors) may result in a violent chemical reaction if a water solution is not used. It is advisable to purify lines by pumping chlorinated water into the piping system - this solution will be non-volatile. Furthermore, dry granular calcium hypochlorite should not be stored or used near solvent cements and primers.

THIS PRODUCT IS NOT FOR USE IN A SYSTEM USING OR BEING TESTED WITH COMPRESSED AIR OR GASSES.

T. Christy Enterprises, Inc.



655 E. Ball Rd. • Anaheim, CA 92805

Tel: (714) 507-3300 • Fax: (714) 507-3310

www.TChristy.com • 800-BLU-GLUE