



## PRODUCT SPECIFICATIONS

Pipe Type	PVC, Schedule 40 & 80
Cement Uses:	For PVC pipe and fitting applications; potable water, pressure, non-pressure, conduit, drain, duct, DWV and sewer
Maximum Diameter	For PVC pipe sizes thru 6" (150mm) all schedules and classes. Schedule 80 thru 4" (100mm)
Color	Aqua Blue
Relative Set Time	Extremely Fast Set
Body	Medium Body
Performance Specification	ASTM D-2564, NSF/ANSI 14, NSF/ANSI 61, NSF/ANSI 372
Brookfield Viscosity	Minimum 500 cP @73°F +/- 2°F 23°C +/- 1°C
Specific Gravity	Typical 0.924 +/- 0.04
Industry Listing	 U.P. Code PW-DWV-SW
Max VOC Emissions	510 g/l per SCAQMD Rule 1168 Method 316A 
Shelf Life	3 Years
LEED Compliant	Low VOC formulation can earn credit toward the U.S. Green Building Council's LEED certification for green buildings. 

## WET OR DRY CONDITIONS PVC PIPE CEMENT

### Stay productive in all weather and site conditions

Installing or repairing in a drizzling rain? Working in a wet valve box? Reach for a great solution, **Christy's Wet or Dry Conditions PVC Cement**. Like the name says, it's formulated to work across a wide range of weather and site conditions.

**Wet or Dry Conditions** sets and cures extremely fast, helping you maximize your productivity.

- For installation or repair in wet or inclement weather conditions. **WET or DRY** is specially formulated to get the job done right!
- A Pro-Grade "Blue Glue" - Premium formulation designed to work in all jobsite conditions
- Extremely fast set and cure times enable maximum productivity
- Can be used without a primer for non-pressure systems up to 6" (150 mm) and pressure systems below 4" (100 mm) if local codes permit
- For PVC pipe and fitting applications; potable water, pressure, non-pressure, conduit, drain, duct, DWV and sewer
- Low VOC

### CASE PACK CONFIGURATIONS

Item #	Can Size	Cans/Cs	Can UPC
RH-WET-QP-24	¼ Pint, 4 oz (118 ml)	24	044752339391
RH-WET-HP-24	½ Pint, 8 oz (237 ml)	24	044752339360
RH-WET-QT-12	Quart, 32 oz (946 ml)	12	044752339407
RH-WET-GL-6	Gallon, 128 oz (3.785 )	6	044752339353

**SPECIAL CONSIDERATIONS:** Consult the SDS for health and safety specifics. Always use in a well-ventilated environment. Wear safety glasses and gloves at all times. **DO NOT USE** a dry granular calcium hypochlorite as a disinfecting material for water purification in potable water piping systems. The introduction of granules or pellets of calcium hypochlorite with PVC and CPVC solvent cements and primers (including their vapors) may result in a violent chemical reaction if a water solution is not used. It is advisable to purify lines by pumping chlorinated water into the piping system - this solution will be non-volatile. Furthermore, dry granular calcium hypochlorite should not be stored or used near solvent cements and primers.

**THIS PRODUCT IS NOT FOR USE IN A SYSTEM USING OR  
BEING TESTED WITH COMPRESSED AIR OR GASSES.**

T. Christy Enterprises, Inc.



655 E. Ball Rd. • Anaheim, CA 92805

Tel: (714) 507-3300 • Fax: (714) 507-3310

www.TChristy.com • 800-BLU-GLUE