



## **PRODUCT SPECIFICATIONS**

Application	For corrosion and abrasion protection on underground or above ground metal pipelines, fittings, joints and electrical conduits.
Adhesion to Steel	>0.57 kg/25mm
Tensile Strength	>16 kg/25mm
Elongation	% >200
Applied Temp. Range	32°F~140°F
Color	Black
Test Method	ASTM D-1000.
Shelf Life	12 months when stored in original carton at 23°F and 65% relative humidity
Availability	Standard 38mm (1.5") i.d. core

## Above figures are for reference and cannot be treated as warranties. Customers are advised to test the material to determine the suitability against intended applications.

IPS Corporation 455 W. Victoria St., Compton, CA 90220 (800) 888-8312 www.tchristy.com

## **Pipe Wrap Tape**

Christy's Pipe Wrap Tape is based on a heavy duty plasticized polyvinyl chloride (PVC) film, coated with an aggressive non-thermosetting rubber-resin adhesive with good aging characteristics. Used for corrosion and abrasion protection on underground or above ground metal pipelines, fittings, joints and electrical conduits.

- Highly anticorrosive and high puncture resistance
- Excellent insulating properties.
- Good ductility and flexibility.



## Available in multiple sizes:

1" x 100' x 10 mil 2" x 100' x 10 mil 2" x 100' x 20 mil 4" x 100' x 10 mil 4" x 100' x 20 mil

THIS PRODUCT IS NOT FOR USE IN A SYSTEM USING OR BEING TESTED WITH COMPRESSED AIR OR GASES.